

Provided by the author(s) and University of Galway in accordance with publisher policies. Please cite the published version when available.

Title	Plane-polarised finite-amplitude shear waves in deformed incompressible materials
Author(s)	Destrade, Michel; Saccomandi, Giuseppe
Publication Date	2022-04-07
Publication Information	Destrade, Michel, & Saccomandi, Giuseppe. (2022). Plane-polarised finite-amplitude shear waves in deformed incompressible materials. Mathematics and Mechanics of Solids, 27(8), 1494-1503. doi:10.1177/10812865221089588
Publisher	SAGE Publications
Link to publisher's version	https://doi.org/10.1177/10812865221089588
Item record	http://hdl.handle.net/10379/18081
DOI	http://dx.doi.org/10.1177/1081286522108958

Downloaded 2024-05-20T00:11:20Z

Some rights reserved. For more information, please see the item record link above.



Plane-polarised finite-amplitude shear waves in deformed incompressible materials

Mathematics and Mechanics of Solids XX(X):2–14
© The Author(s) 0000
Reprints and permission:
sagepub.co.uk/journalsPermissions.nav
DOI: 10.1177/ToBeAssigned
www.sagepub.com/

SAGE

Michel Destrade^{1,2} and Giuseppe Saccomandi^{3,1}

Abstract

We investigate how two finite-amplitude, transverse, plane body waves may be superposed to propagate in a deformed hyperelastic incompressible solid. We find that the equations of motion reduce to a well-determined system of partial differential equations, making the motion controllable for all solids. We find that in deformed Mooney-Rivlin materials, they may travel along any direction and be polarised along any transverse direction, an extension of a result by Boulanger and Hayes [Quart. J. Mech. Appl. Math. 45 (1992) 575]. Furthermore, their motion is governed by a linear system of partial differential equations, making the Mooney-Rivlin special in that respect. We select another model to show that for other materials, the equations are nonlinear. We use asymptotic equations to reveal the onset of nonlinearity for the waves, paying particular attention to how close the propagation direction is to the principal axes of pre-deformation.

Dedicated to the late Hui-Hui Dai, a true gentleman, always kind, sincere and generous; greatly missed.

1 Introduction

In 1969, Currie and Hayes [4] showed that two linearly polarised finite-amplitude transverse waves, polarised in two orthogonal directions, may propagate along any direction in a Mooney-Rivlin material maintained in a state of arbitrary static finite homogeneous deformation. Their results were a generalisation, to some extent, of previous findings contained by Green [11] and Carroll [3]. Later, beginning with a paper published in 1992 [1], Boulanger and Hayes wrote a series of papers to investigate and extend those results further, in a deep and elegant manner; their findings were collected and summarised in the survey [2].

Boulanger and Hayes's main finding is that if \boldsymbol{B} denotes the left Cauchy-Green deformation tensor of the homogeneous pre-deformation and \boldsymbol{n} denotes the direction of propagation, then the directions of polarisation of the two possible transverse waves propagating along \boldsymbol{n} must be along the principal axes of the elliptical section of the $\boldsymbol{x} \cdot \boldsymbol{B}^{-1} \boldsymbol{x} = 1$ ellipsoid by the $\boldsymbol{x} \cdot \boldsymbol{n} = \boldsymbol{0}$ plane. That restriction is in place for the class of Mooney-Rivlin materials, that is, those incompressible, homogeneous, isotropic materials with strain energy density of the form $W = C(I_1 - 3) + E(I_2 - 3)$, where I_1 and I_2 are the first and second principal invariants of \boldsymbol{C} , the right Cauchy-Green deformation tensor, and C, E are positive constants. Only in the special case of a neo-Hookean material, when $C_2 = 0$, may the directions of polarisation be along any direction orthogonal to \boldsymbol{n} .

This result is the natural consequence of the propagation condition,

$$\mathbf{a} \cdot \mathbf{B}^{-1} \mathbf{b} = 0, \tag{1}$$

where (n, a, b) is an orthonormal triad, with n the direction of propagation. This condition is satisfied when the vectors a and b are aligned with the axes of the central elliptic section of the ellipsoid by the plane $n \cdot x = 0$. Then two single transverse waves may propagate individually, one polarised along a, the other along b. The propagation condition (1) follows from the equations of motion: these turn out to be an overdetermined system of three

Corresponding author:

Michel Destrade, School of Mathematical and Statistical Sciences, NUI Galway.

Email: michel.destrade@nuigalway.ie

¹School of Mathematical and Statistical Sciences, NUI Galway, Ireland.

²Department of Engineering Mechanics, Zhejiang University, Hangzhou 310027, PR China.

³Dipartimento di Ingegneria, Università degli Studi di Perugia and Sezione INFN of Perugia, Italy.

partial differential equations for two unknowns functions, the pressure field and the transverse linearly-polarized wave function. To reduce the system to two equations for two unknowns, the propagation condition (1) must apply.

Another result established by Boulanger and Hayes [1] concerns the superposition of two waves which propagate along the same direction n. Indeed, they found that for any propagation direction n, two waves could propagate and solve the equations of motion simultaneously if they were linearly polarised along the unit vectors a and b solutions to Equation (1). This is a remarkable result, because no assumption is made about the magnitude of the waves, and the theory is completely non-linear and exact.

In the present note we show that if we consider two shear waves propagating along any direction n and polarized along any orthogonal unit vectors a and b in the $n \cdot x = 0$ plane (not necessarily satisfying (1)), in any deformed hyperelastic material (not just the Mooney-Rivlin materials), then the equations of motion reduce to a well-determined system of partial differential equations. It follows that this motion is controllable for any incompressible and isotropic hyperelastic material. This is shown in the next section.

Further, we find in Section 3 that in the special case of a Mooney-Rivlin material, the determining equations are linear and they possess solutions of permanent form, similar to what was seen in [1], but here for shear waves polarised along any orthogonal unit vectors \boldsymbol{a} and \boldsymbol{b} .

Finally in Section 4, we take a specific form of the strain energy density to study an example of the nonlinear equations generated when the solid is not as special as the one modelled by the Mooney-Rivlin material. We use asymptotic expansions in the amplitude to reveal the onset of nonlinearity in the equations of motion, and how great care must be taken when the direction of propagation is close to, or along a principal axis of pre-deformation.

2 Superposition of two shear waves

Let X be the position vector of a particle in a hyperelastic body in the reference configuration, and x be its position vector in the current configuration. We call $\mathbf{F} = \partial x/\partial X$ the deformation gradient and $\mathbf{B} = \mathbf{F}\mathbf{F}^T$, $\mathbf{C} = \mathbf{F}^T\mathbf{F}$ the left and right Cauchy-Green deformation tensors, respectively.

We consider homogeneous, incompressible (det $\mathbf{F} = 1$ at all times), isotropic and hyperelastic materials, so that their strain-energy density W (measured per unit volume in the undeformed state) is a function of the

form

$$W = W(I_1, I_2), \tag{2}$$

where $I_1 = \operatorname{tr} \mathbf{C}$ and $I_2 = \operatorname{tr} \mathbf{C}^{-1}$ are the first and second principal invariants of \mathbf{C} , respectively. Then the Cauchy stress \mathbf{T} is

$$T = -pI + 2W_1B - 2W_2B^{-1}, (3)$$

where p is the Lagrange multiplier associated with the constraint of incompressibility, and $W_k = \partial W/\partial I_k$. The equations of motion, in the absence of body forces, are

$$\operatorname{div} \mathbf{T} = \rho \, \partial^2 \mathbf{x} / \partial t^2, \tag{4}$$

where ρ is the mass density (which is constant, because of incompressibility). First we consider that the solid is subject to a static finite homogeneous deformation:

$$\overline{\boldsymbol{x}} = \overline{\boldsymbol{F}} \boldsymbol{X},\tag{5}$$

where \overline{F} is a constant tensor, such that $\det \overline{F} = 1$ (to accommodate the constraint of incompressibility). Because this deformation is universal, the stress tensor required to support it is, according to (3),

$$\overline{T} = -\overline{p}I + 2W_1(\overline{I}_1, \overline{I}_2)\overline{B} - 2W_2(\overline{I}_1, \overline{I}_2)\overline{B}^{-1}.$$
 (6)

Taking the Lagrange multiplier \overline{p} to be a constant ensures that the equations of static equilibrium div $\overline{T} = 0$ are satisfied.

Then we superimpose on this deformation two plane homogeneous body shear waves, both propagating along the direction of the unit vector n, with one polarised along a (a unit vector orthogonal to n) and one along $b = n \times a$. Hence this motion is of the form

$$\boldsymbol{x} = \overline{\boldsymbol{x}} + f(\overline{\eta}, t)\boldsymbol{a} + g(\overline{\eta}, t)\boldsymbol{b}, \qquad p = \overline{p} + q(\overline{\eta}, t),$$
 (7)

where $(\overline{\eta}, \overline{\xi}, \overline{\zeta})$ are the components of \overline{x} in the (n, a, b) orthonormal basis, and f, g, q are yet unknown amplitude functions.

The deformation gradient associated with this motion is

$$F = (I + f_{\overline{\eta}} \mathbf{a} \otimes \mathbf{n} + g_{\overline{\eta}} \mathbf{b} \otimes \mathbf{n}) \overline{F}, \tag{8}$$

where the subscript denotes partial differentiation. Clearly, this is an isochoric motion, respecting the constraint of incompressibility.

Let (η, ξ, ζ) be the components of the position vector \boldsymbol{x} in $(\boldsymbol{n}, \boldsymbol{a}, \boldsymbol{b})$. Then the motion $(7)_1$ reads

$$\eta = \overline{\eta}, \quad \xi = \overline{\xi} + f(\eta, t), \quad \zeta = \overline{\zeta} + g(\eta, t).$$
(9)

We then compute the following kinematic quantities associated with the motion,

$$\mathbf{B} = (\mathbf{I} + f_{\eta} \mathbf{a} \otimes \mathbf{n} + g_{\eta} \mathbf{b} \otimes \mathbf{n}) \, \overline{\mathbf{B}} \, (\mathbf{I} + f_{\eta} \mathbf{n} \otimes \mathbf{a} + g_{\eta} \mathbf{n} \otimes \mathbf{b}) \,,$$

$$\mathbf{B}^{-1} = (\mathbf{I} - f_{\eta} \mathbf{n} \otimes \mathbf{a} - g_{\eta} \mathbf{n} \otimes \mathbf{b}) \, \overline{\mathbf{B}}^{-1} \, (\mathbf{I} - f_{\eta} \mathbf{a} \otimes \mathbf{n} - g_{\eta} \mathbf{b} \otimes \mathbf{n}) \,,$$

$$I_{1} = \overline{I}_{1} + 2(f_{\eta} \, \mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{a} + g_{\eta} \, \mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{b}) + (f_{\eta}^{2} + g_{\eta}^{2}) \, \mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n},$$

$$I_{2} = \overline{I}_{2} - 2 \left(f_{\eta} \, \mathbf{n} \cdot \overline{\mathbf{B}}^{-1} \mathbf{a} + g_{\eta} \, \mathbf{n} \cdot \overline{\mathbf{B}}^{-1} \mathbf{b} \right) + f_{\eta}^{2} \, \mathbf{a} \cdot \overline{\mathbf{B}}^{-1} \mathbf{a} + g_{\eta}^{2} \, \mathbf{b} \cdot \overline{\mathbf{B}}^{-1} \mathbf{b}.$$
(10)

Now the equations of motion (4), written in the basis (n, a, b), reduce to

$$0 = \frac{\partial T_{\eta\eta}}{\partial \eta}, \qquad \rho f_{tt} = \frac{\partial T_{\xi\eta}}{\partial \eta}, \qquad \rho g_{tt} = \frac{\partial T_{\zeta\eta}}{\partial \eta}. \tag{11}$$

The first of these is satisfied by an appropriate choice of the Lagrange multiplier q, which then can be forgotten about, as it does not play any role in the other two equations.

Introducing the notation $W = W(I_1, I_2)$ where I_1 and I_2 are now given by (10), we compute the remaining non-zero components of the stress tensor as

$$T_{\xi\eta} = 2W_1 \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a} + f_{\eta} \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} \right)$$

$$-2W_2 \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} - f_{\eta} \, \boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} - g_{\eta} \, \boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right), \quad (12)$$

and

$$T_{\zeta\eta} = 2W_1 \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b} + g_{\eta} \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} \right)$$
$$- 2W_2 \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} - f_{\eta} \, \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} - g_{\eta} \, \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right), \quad (13)$$

where $W_k = \partial W/\partial I_k$.

It is now clear that the remaining equations of motion $(11)_{2,3}$ are a nonlinear system of two coupled differential equations for the two unknown functions f and g and thus, that the motion is controllable for any incompressible, isotropic, hyperelastic material.

3 The special case of Mooney-Rivlin materials

Consider now the special case of Mooney-Rivlin materials, with strain energy density

$$W = C(I_1 - 3) + E(I_2 - 3), (14)$$

where C, E are material constants such that C > 0 and $E \ge 0$.

For these materials the system of equations $(11)_{2,3}$, is *linear*, as the equations read

$$\rho f_{tt} = \left(C \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} + E \, \boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} \right) f_{\eta \eta} + E \left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right) g_{\eta \eta},$$

$$\rho g_{tt} = \left(C \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} + E \, \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right) g_{\eta \eta} + E \left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right) f_{\eta \eta}. \tag{15}$$

As noted by Boulanger and Hayes [1], these equations decouple when $\mathbf{a} \cdot \overline{\mathbf{B}}^{-1} \mathbf{b} = 0$. But because (15) is a linear system, we may in fact solve it in any case, by writing it as

$$\rho \begin{bmatrix} f \\ g \end{bmatrix}_{tt} = \begin{bmatrix} C \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} + E \, \boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} & E \, \boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \\ E \, \boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} & C \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} + E \, \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \end{bmatrix} \begin{bmatrix} f \\ g \end{bmatrix}_{\eta\eta}, \quad (16)$$

and diagonalising the matrix. We then arrive at the decoupled equations

$$\rho u_{tt} = \lambda_1 u_{\eta\eta}, \qquad \rho v_{tt} = \lambda_2 v_{\eta\eta}, \tag{17}$$

where the (real) eigenvalues are

$$\lambda_{1,2} = \frac{1}{2} \left[2C \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} + E \left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} + \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right) \right]$$

$$\pm E \sqrt{\left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} - \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right)^{2} + 4 \left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b} \right)^{2}} \right]. \quad (18)$$

and the functions u, v are defined by

$$\begin{bmatrix} u \\ v \end{bmatrix} = \begin{bmatrix} \cos \theta & \sin \theta \\ -\sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} f \\ g \end{bmatrix}, \text{ with } \tan 2\theta = \frac{2 \, \boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b}}{\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} - \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b}}.$$
(19)

Note that both eigenvalues are positive, because λ_1 is the sum of positive quantities, and writing that $\lambda_2 > 0$ is equivalent to

$$C^{2} \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}\right)^{2} + CE \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}\right) \left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a} + \boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b}\right) + E^{2} \left[\left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{a}\right) \left(\boldsymbol{b} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b}\right) - \left(\boldsymbol{a} \cdot \overline{\boldsymbol{B}}^{-1} \boldsymbol{b}\right)^{2}\right] > 0, \quad (20)$$

which is always true, because the last bracketed term is $|V^{-1}a \times V^{-1}b|^2$, where V is the square root of B.

Both u and v satisfy the wave equation (17), with general solution

$$u = u_{-}(\eta - c_1 t) + u_{+}(\eta + c_1 t), \qquad v = v_{-}(\eta - c_2 t) + v_{+}(\eta + c_2 t),$$
 (21)

where u_{\pm} , v_{\pm} are arbitrary functions, and the speeds are $c_i = \sqrt{\lambda_i/\rho}$.

Hence we have established that we may use Boulanger and Hayes's solution (where \boldsymbol{a} and \boldsymbol{b} satisfy (1)) to generate a solution with any direction of polarization. Morevover, the motion thus generated has components which travel at different speeds c_1 and c_2 .

To conclude this section, we note that for Mooney-Rivlin materials, the determining equations for transverse waves are a completely exceptional hyperbolic system, once the strong ellipticity condition is ensured, see [20]. The possibility of wave motion as solution to linear partial differential equations for the Mooney-Rivlin and neo-Hookean materials is not restricted to the case of transverse waves, as has been noticed by several authors, including Lei and Hung [14], Rajagopal [18], and Hill and Dai [12].

4 Nonlinear waves

Finite amplitude plane waves propagating in a deformed Mooney-Rivlin material lead to an exceptional hyperbolic system, as the motion is determined by a linear system of partial differential equations. Here we turn our attention to materials which are not special in that respect. It leads us to a nonlinear hyperbolic system, which we approach using asymptotic expansions.

First we consider the *case of no pre-strain*, so that $\overline{B} \equiv I$ and

$$T_{\xi\eta} = 2(\mathcal{W}_1 + \mathcal{W}_2)f_{\eta}, \qquad T_{\zeta\eta} = 2(\mathcal{W}_1 + \mathcal{W}_2)g_{\eta}. \tag{22}$$

Introducing the unknown functions $\hat{F} = f_{\eta}$, $\hat{G} = g_{\eta}$, we have $I_1 = I_2 = F^2 + G^2 + 3$, and the remaining two determining equations in (11) may be rewritten as

$$\rho \hat{F}_{tt} = (\mathcal{Q}\hat{F})_{\eta\eta}, \qquad \rho \hat{G}_{tt} = (\mathcal{Q}\hat{G})_{\eta\eta}, \tag{23}$$

where $Q = 2(W_1 + W_2)$ is the generalized shear modulus. Clearly $Q = Q(\hat{F}^2 + \hat{G}^2)$. Then considering that the amplitudes are small, we write $\hat{F} = \epsilon F$ and $\hat{G} = \epsilon G$ where $|\epsilon| \ll 1$ and expand Q as $Q = \mu_0 + \mu_1 \epsilon^2 (F^2 + G^2) + \dots$ For the Mooney-Rivlin material, $\mu_0 = 2(C + E)$ and $\mu_1 = \mu_2 = 0$

... = 0, but in general, $\mu_1 \neq 0$ (although there are materials other than the Mooney-Rivlin material such that $\mu_1 = \mu_2 = \ldots = 0$, see [16].) In that case we introduce the scaled time and space variables

$$\tau = \epsilon^2 t, \qquad x = \alpha^{-1} \eta - ct, \tag{24}$$

where $c = \sqrt{\mu_0/\rho}$ is the speed of sound in the solid, and α is a suitable constant to be determined later. It is then possible to derive an $\mathcal{O}(\epsilon^3)$ asymptotic reduction of (23), as

$$F_{\tau} + \beta [(F^2 + G^2)F]_x = 0, \quad G_{\tau} + \beta [(F^2 + G^2)C]_x = 0,$$
 (25)

where β is a constant expressed in terms of ρ , μ_0 and μ_1 . Vitolo and Saccomandi [20] discuss in detail the mathematical and geometrical structures of the system (23) and of the corresponding asymptotic system (25). Note in particular that (25) is a Temple system, for which a general solution can be found using a generalized hodograph transformation [19].

Next we derive the asymptotic system of governing equations in the case of a pre-strain applied to a specific class of materials. Here we restrict attention to materials with a strain-energy density of the form [15, 8]

$$W = \frac{\mu_0}{2} \left[I_1 - 3 + \frac{\kappa}{2} (I_1^2 - 3^2) \right], \tag{26}$$

where $\mu_0 > 0$ is the infinitesimal shear modulus and $\kappa > 0$ is a measure of the departure from the new-Hookean model, in other words, a nonlinearity parameter with respect to wave propagation. Then with $\hat{F} = \epsilon F$ and $\hat{G} = \epsilon G$ where $|\epsilon| \ll 1$, we differentiate the equations of motion (11) with respect to η to obtain the determining equations as

$$\rho \epsilon F_{tt} = [2W_1 \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a} + \epsilon F \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} \right)]_{\eta \eta},$$

$$\rho \epsilon G_{tt} = [2W_1 \left(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b} + \epsilon G \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} \right)]_{\eta \eta},$$
(27)

where

$$2W_1 = \mu_0 \left[1 + \kappa \overline{I}_1 + 2\epsilon \kappa (F \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a} + G \, \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b}) + \epsilon^2 \kappa \left(F^2 + G^2 \right) \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} \right].$$
(28)

We first consider that $n \cdot \overline{B}a$ and $n \cdot \overline{B}b$ are of order $\mathcal{O}(1)$ (for a detailed discussion about this point, see Pucci et al. [17]). In this case the first nonlinearity arises at order ϵ^2 . We introduce the scaled time and space

variables

$$\tau = \epsilon t, \qquad x = \alpha^{-1} \eta - ct, \tag{29}$$

where $c = \sqrt{\mu_0/\rho}$ is the speed of infinitesimal shear waves in the undeformed material and the non-dimensional constant α is to be determined soon. We then obtain the following equations,

$$(\boldsymbol{M} - \alpha^2 \boldsymbol{I}) \begin{bmatrix} F \\ G \end{bmatrix}_{xx} = 2\epsilon c^{-1} \begin{bmatrix} F \\ G \end{bmatrix}_{\tau x} + 2\epsilon \kappa (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) \left\{ \boldsymbol{N} \begin{bmatrix} F \\ G \end{bmatrix}_{x} \right\}_{x} + \dots, \quad (30)$$

where M is a constant matrix,

$$M = \begin{bmatrix} (1 + \kappa \overline{I}_1)(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) + 2\kappa (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})^2 & 2\kappa (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b}) \\ 2\kappa (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b}) & (1 + \kappa \overline{I}_1)(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) + 2\kappa (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})^2 \end{bmatrix},$$
(31)

and N depends on F and G,

$$N = \begin{bmatrix} 3(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})F + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})G & (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})F + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})G \\ (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})F + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})G & (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})F + 3(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})G \end{bmatrix}.$$
(32)

Expanding now F and G as

$$F = F_0(\tau, x) + \epsilon F_1(\tau, x) + \dots, \qquad G = G_0(\tau, x) + \epsilon G_1(\tau, x) + \dots,$$
 (33)

we then find the following equations at order ϵ^0 :

$$(\boldsymbol{M} - \alpha^2 \boldsymbol{I}) \begin{bmatrix} F_0 \\ G_0 \end{bmatrix}_{xx} = \boldsymbol{0}, \tag{34}$$

and at order ϵ^1 :

$$(\boldsymbol{M} - \alpha^2 \boldsymbol{I}) \begin{bmatrix} F_1 \\ G_1 \end{bmatrix}_{xx} = 2 \left\{ c^{-1} \begin{bmatrix} F_0 \\ G_0 \end{bmatrix}_{\tau} + \kappa (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) \boldsymbol{N}_0 \begin{bmatrix} F_0 \\ G_0 \end{bmatrix}_{x} \right\}_{x}, \quad (35)$$

where N_0 is N in (32) when F, G are replaced by F_0 , G_0 , respectively.

The system (34) is an eigen-problem, with M symmetric. The eigenvalues are both positive:

$$\alpha_1^2 = (1 + \kappa \overline{I}_1)(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}),$$

$$\alpha_2^2 = (1 + \kappa \overline{I}_1)(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) + 2\kappa [(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})^2 + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})^2],$$
(36)

with corresponding eigenvectors parallel to

$$v_1 = \begin{bmatrix} \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b} \\ -\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a} \end{bmatrix}, \qquad v_2 = \begin{bmatrix} \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a} \\ \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b} \end{bmatrix},$$
 (37)

respectively. It follows upon integration that F_0 , G_0 are found as

$$\begin{bmatrix} F_0 \\ G_0 \end{bmatrix} = \phi(\tau, x) \boldsymbol{v}_1 \quad \text{with} \quad x = \alpha_1^{-1} \eta - ct,$$
 (38)

or

$$\begin{bmatrix} F_0 \\ G_0 \end{bmatrix} = \psi(\tau, x) \boldsymbol{v}_2 \quad \text{with} \quad x = \alpha_2^{-1} \eta - ct, \tag{39}$$

depending on which value is chosen for α in the scaling (29), where ϕ , ψ are arbitrary functions.

Taking now the dot product of (35) with v_i (i = 1, 2), we arrive at

$$[(\boldsymbol{v}_{1}\cdot\boldsymbol{v}_{1})\phi_{\tau} + \kappa c(\boldsymbol{n}\cdot\overline{\boldsymbol{B}}\boldsymbol{n})(\boldsymbol{v}_{1}\cdot\boldsymbol{N}_{0}\boldsymbol{v}_{1})\phi_{x}]_{x} = 0,$$

$$[(\boldsymbol{v}_{2}\cdot\boldsymbol{v}_{2})\psi_{\tau} + \kappa c(\boldsymbol{n}\cdot\overline{\boldsymbol{B}}\boldsymbol{n})(\boldsymbol{v}_{2}\cdot\boldsymbol{N}_{0}\boldsymbol{v}_{2})\psi_{x}]_{x} = 0,$$
(40)

which we integrate with respect to x. Simple calculations show that $\mathbf{v}_1 \cdot \mathbf{N}_0 \mathbf{v}_1 = 0$, so that taking $\alpha = \alpha_1$ in the scaling (29) leads to a *linearly degenerate wave* [13]. On the other hand, $\mathbf{v}_2 \cdot \mathbf{N}_0 \mathbf{v}_2 \neq 0$, and in that case we find a *genuinely nonlinear wave* [13], governed by the equation

$$\psi_{\tau} + 3\kappa c(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n})[(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})^{2} + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})^{2}]\psi\psi_{x} = 0. \tag{41}$$

Using the function $\overline{\psi} = 3\kappa c(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n})[(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a})^2 + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b})^2]\psi$, we see that this is the *inviscid Burgers equation*,

$$\bar{\psi}_{\tau} + \left(\frac{1}{2}\bar{\psi}^2\right)_x = 0. \tag{42}$$

Finally, we consider the case where the direction of propagation of the wave is close to a principal direction, in the sense that $\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a}$ and $\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b}$ are of order $\mathcal{O}(\epsilon)$, say $\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{a} = \epsilon \boldsymbol{a}$ and $\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{b} = \epsilon \boldsymbol{b}$, where \boldsymbol{a} , \boldsymbol{b} are constants of order ϵ^0 .

Then the scaling (29) does not lead to a consistent expansion. As pointed out by Pucci et al. [17] for the case of a single shear wave, the first nonlinearity arises at order ϵ^3 , as we must now use the variables

$$\tau = \epsilon^2 t, \qquad x = \alpha^{-1} \eta - ct. \tag{43}$$

Then we find that

$$2W_1 = \mu_0 (1 + \kappa \overline{I}_1 + \kappa \epsilon^2 \Lambda), \tag{44}$$

where

$$\Lambda = 2aF + 2bG + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) \left(F^2 + G^2 \right). \tag{45}$$

At order ϵ we obtain the decoupled system

$$\alpha^{2} F_{xx} = (1 + \kappa \overline{I}_{1})(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) F_{xx}, \qquad \alpha^{2} G_{xx} = (1 + \kappa \overline{I}_{1})(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) G_{xx}$$
 (46)

which fixes α as $\alpha = \sqrt{(1 + \kappa \overline{I}_1)(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n})}$.

The next terms are at order ϵ^3 , giving, upon integration, the system

$$\alpha^{2} F_{\tau} + \kappa c [(a + \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} F)\Lambda]_{x} = 0,$$

$$\alpha^{2} G_{\tau} + \kappa c [(b + \boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n} G)\Lambda]_{x} = 0.$$
 (47)

This coupled system contains both second- and third-order non-linearities. It is consistent with the system (25) when \boldsymbol{a} and \boldsymbol{b} are aligned with the principal axes of $\overline{\boldsymbol{B}}$. It can be written in the form

$$\alpha^2 \begin{bmatrix} F \\ G \end{bmatrix}_{\tau} + \kappa c \, \boldsymbol{A} \begin{bmatrix} F \\ G \end{bmatrix}_{\tau} = 0, \tag{48}$$

where

$$\mathbf{A} = \begin{bmatrix} (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n}) \Lambda + 2[a + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{b}) F]^2 & 2[a + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n}) F][b + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n}) G] \\ 2[a + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n}) F][b + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n}) G] & (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n}) \Lambda + 2[b + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{b}) G]^2 \end{bmatrix},$$
(49)

is symmetric and easy to diagonalise. We find that the eigenvalues are

$$\lambda_1 = (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) \Lambda, \qquad \lambda_2 = 2(a^2 + b^2) + 3(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) \Lambda,$$
 (50)

with corresponding eigenvectors parallel to

$$\begin{bmatrix} b + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n})G \\ -a - (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n})F \end{bmatrix}, \qquad \begin{bmatrix} a + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n})F \\ b + (\mathbf{n} \cdot \overline{\mathbf{B}} \mathbf{n})G \end{bmatrix}, \tag{51}$$

respectively. We find the Riemann invariants as

$$R = \frac{a + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) F}{b + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) G}, \qquad S = 2aF + 2bG + (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) (F^2 + G^2). \tag{52}$$

Therefore, bringing together (45), (50) and (52), we conclude that the eigenvalues are written in terms of the Riemann invariants as

$$\lambda_1 = (\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) S, \qquad \lambda_2 = 2(a^2 + b^2) + 3(\boldsymbol{n} \cdot \overline{\boldsymbol{B}} \boldsymbol{n}) S,$$
 (53)

and that the system is easily integrable in the hodograph plane.

5 Concluding remarks

Boulanger and Hayes were interested in the propagation of finite-amplitude shear waves in homogeneously deformed Mooney-Rivlin materials. They found that their motion is governed by linear differential equations and that, for a given propagation direction \boldsymbol{n} , only two directions of polarization are possible, those aligned with the principal axes of the elliptical section of the $\boldsymbol{x} \cdot \bar{\boldsymbol{B}} \boldsymbol{x} = 1$ ellipsoid by the $\boldsymbol{n} \cdot \boldsymbol{x} = 0$ plane. Then they turned their attention to the linear superposition of such two shear waves, in the process missing the generality that it is always possible to superpose two shear waves polarized in any direction $\boldsymbol{a} \perp \boldsymbol{n}$ (and $\boldsymbol{b} = \boldsymbol{n} \times \boldsymbol{a}$).

In fact, we found here that this result is valid for any isotropic strainenergy density function, not just the Mooney-Rivlin class. Moreover, we also complemented the results of the recent paper by Pucci et al. [17]. The important findings in the full nonlinear setting are that the first nonlinearity that matters in pre-strained materials for shear waves is of second order, and that when the waves propagate and are polarized along, or close to, principal axes, (including the case $\overline{B} = I$), the first nonlinearity encountered is of third order.

The advantage of using the asymptotic first-order equations (42) and (47) as compared to the full second-order equations is that they lend themselves to be solved using a plethora of analytical methods [5]. We did not pursue this avenue here, as it was beyond the scope of this short note. We nonetheless point out that adding a dissipative term to our constitutive equations, as in [6], would lead to a dissipative Burgers equation for (42) and a system of modified Burgers equations for (47). On the other hand, adding a dispersive term, as in [7], would turn (42) into a KdV equation and the system (47) into a set of coupled Gardner equations [9, 10]. This is a remarkable fact, because Gardner's equation was introduced as a sort of mathematical 'toy', and it is quite rare to encounter such an esoteric equation in the modelling of physics phenomena such as wave propagation.

Funding

The research of MD was supported by a 111 Project for International Collaboration (Chinese Government, PR China) No. B21034 and by a grant from the Seagull Program (Zhejiang Province, PR China). GS is supported by the Istituto Nazionale di Alta Matematica (INdAM), Fondi di Ricerca di Base UNIPG, the MIUR- PRIN project 2017KL4EF3 and Istituto Nazionale di Fisica Nucleare through its IS 'Mathematical Methods in Non-Linear Physics'.

References

- [1] Boulanger, P., & Hayes, M. (1992). Finite-amplitude waves in deformed Mooney-Rivlin materials. The Quarterly Journal of Mechanics and Applied Mathematics, 45(4), 575-593.
- [2] Boulanger, P., & Hayes, M. (2001). Finite-amplitude waves in Mooney-Rivlin and Hadamard materials. In Topics in finite elasticity (pp. 131-167). Springer, Vienna.
- [3] Carroll, M. M. (1967). Some results on finite amplitude elastic waves. Acta Mechanica, 3(2), 167-181.
- [4] Currie, P., & Hayes, M. (1969). Longitudinal and transverse waves in finite elastic strain. Hadamard and Green materials. IMA Journal of Applied Mathematics, 5(2), 140-161.
- [5] Dafermos, C. M. (2005). Hyperbolic conservation laws in continuum physics. Berlin: Springer.
- [6] Destrade, M., & Saccomandi, G. (2005). Finite amplitude elastic waves propagating in compressible solids. Physical Review E, 72(1), 016620.
- [7] Destrade, M., & Saccomandi, G. (2008). Nonlinear transverse waves in deformed dispersive solids. Wave Motion, 45(3), 325-336.
- [8] Destrade, M., Saccomandi, G. & Sgura, I. (2017). Methodical fitting for mathematical models of rubber-like materials. Proceedings of the Royal Society A, 473(2198), 20160811.
- [9] Gardner, C. S., Greene, J. M., Kruskal, M. D., & Miura, R. M. (1974). Korteweg-de Vries equation and generalizations. VI. methods for exact solution. Communications on Pure and Applied Mathematics, 27(1), 97-133.
- [10] Coclite, G.M., Maddalena, F., Puglisi, G., Romano, M., & Saccomandi, G. (to appear). The Gardner equation in elastodynamics. SIAM Journal of Applied Mathematics.
- [11] Green, A. E. (1963). A note on wave propagation in initially deformed bodies. Journal of the Mechanics and Physics of Solids, 11(2), 119-126.

- [12] Hill, J. M., & Dai, H. H. (2002). Nonlinear plane waves in finite deformable infinite Mooney elastic materials. Journal of Elasticity, 67(2), 71-80.
- [13] Hunter, J. K. (1995). Asymptotic equations for nonlinear hyperbolic waves. In *Surveys in Applied Mathematics* (pp. 167-276). Springer, Boston, MA.
- [14] Lei, H. C., & Hung, M. J. (1997). Linearity of waves in some systems of non-linear elastodynamics. International journal of non-linear mechanics, 32(2), 353-360.
- [15] Lopez-Pamies, O. (2010). A new I_1 -based hyperelastic model for rubber elastic materials. Comptes Rendus Mécanique, 338(1), 3-11.
- [16] Mangan, R., Destrade, M., & Saccomandi, G. (2016). Strain energy function for isotropic non-linear elastic incompressible solids with linear finite strain response in shear and torsion. Extreme Mechanics Letters 9, 204-206.
- [17] Pucci, E., Saccomandi, G., & Vergori, L. (2019). Linearly polarized waves of finite amplitude in pre-strained elastic materials. Proceedings of the Royal Society A, 475(2226), 20180891.
- [18] Rajagopal, K. R. (1998). On a class of elastodynamic motions in a neo-Hookean elastic solid. International Journal of Non-Linear Mechanics, 33(3), 397-405.
- [19] Tsarev, S. P. (1991). The geometry of Hamiltonian systems of hydrodynamic type. The generalized hodograph method, Mathematics of the USSR-Izvestiya, 37(2), 397-419.
- [20] Saccomandi, G., & Vitolo, R. (2014). On the mathematical and geometrical structure of the determining equations for shear waves in nonlinear isotropic incompressible elastodynamics. Journal of Mathematical Physics, 55(8), 081502.
- [21] Zabolotskaya, E. A., Hamilton, M. F., Ilinskii, Y. A., & Meegan, G. D. (2004). Modeling of nonlinear shear waves in soft solids. The Journal of the Acoustical Society of America, 116(5), 2807-2813.